

## PWJDM Nissan GT-R Dry Carbon Door Sills

### Installation Guide

This install will take ~2 hours depending on how familiar you are with your car and tools. You will likely need to lift your car in order to remove the sidesill panels so make sure you have access to a lift or properly rest the car on jackstands. Never prop a car up by a jack only, if the jack fails you will be injured or killed.

\*\*We suggest you have a container handy to hold all the screws, bolts, and plastic fasteners. Many will be re-used.

\*\* There are many plastic pop out fasteners on this car. Although a flat head screwdriver can work in most cases for removing these, you do run the risk of splitting the head off a plastic fastener. We recommend the use of a proper bodyclip remover which looks like a very thin and wide flathead with a slot cut into it.

Before Installation, double check to make sure you have all these components.

| ITEM# | QTY | COMPONENT DESCRIPTION                   |
|-------|-----|---|
| 1     | 1   | PWJDM carbon door sills, left and right |
| 2     | 1   | Install manual                          |

#### 1. Remove the exterior sidesills/sideskirts.

- With the car properly resting, remove both exterior sidesill/sideskirt panels from the car.

#### 2. Remove the stock door sills.

- Pop out the plastic fasteners that keep the door sill on the side of the car.



- Remove the inner plastic door sill panel.

- Lift up the appropriate amount of the rubber door seal to allow the door sill to come off.



### 3. Installing the carbon door sills.

- a. Notice the Password:JDM logo is supposed to be installed towards the back of the car.
- b. Remove the backing from the Velcro tape on the carbon pieces. This tape is used to keep vibration noise down and allow adjustments.



- c. Align the carbon sill holes with the holes in the car and stick the piece to the car. Press firmly against the carbon so the Velcro tape sticks well to the car.
- d. If the holes don't line up just pull it off and move it as necessary.
- e. Pop in the plastic fasteners to secure the door sill.



### 4. Reinstall everything.

- a. Reinstall the inner doorsills, and replace the door seal.
- b. Reinstall the outer side sills.
- c. Now impress your friends with the sweet carbon.